

Serving the Hospitality Industry with Advanced IP and Analog Telephony Solutions Worldwide

ASP-6110-SF

Single Line Analog Phone

- Single line analog phone.
- Half duplex speakerphone.
- 10 customizable service dials.
- Message waiting key with indicator.
- Customizable hotel logo and service dials.
- Support FSK Message Waiting Signal Type

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At AEi your satisfaction is our priority.





AEi- Corporate Office Millbrae, California U.S.A Sales: +1.650.552.9416 sales@aeicommunications.com AEi- CALA Office

Lima, Peru Sales : +51.9.8257.6251 cala@aeicommunications.com AEi- Asia Pacific Office New Taipei City, Taiwan Sales : +886.2.2696.8809 asiapac@aeicommunications.com

AEi- EMEA Office

London, United Kingdom Budva, Mo Sales : +44 (0)1753.643736 Sales : +38 emea@aeicommunications.com eastern.eu

AEi- Southern Asia Office Penang, Malaysia Sales : +604.3994341 so.asia@aeicommunications.com

AEi- CEE&CIS Office Budva, Montenegro Sales : +3826981251 eastern.europe@aeicommunications.com

1. Features Keys (0~9, *, #) **Dial keys** • Speaker, Mute, Redial, Flash, Message and Volume up/down Function keys Programmable Keys 10 Service dial keys Phone Features Mute and Resume Handset, Speaker volume control . 10 programmable services dials Ringer volume switch Programmable flash timing Redial last call

Red color message waiting indicator for ringing and message waiting

2. Hardware Specifications

LED Indications	٠	Speaker, Mute keys and Message waiting indicator
Power	•	Telephone line powered
Jacks	٠	RJ11 PSTN jack x 2, RJ9 Handset jack x1,
Ring Voltage	•	40V RMS minimum
Line Cord	٠	10 feet x 1
Size and Weight	٠	Dimensions:227mm(L) x158mm(W) x 141mm(H), Weight: 835g
Message Waiting Signal Type	٠	FSK, High Voltage, Low Voltage, Reverse Polarity

3.	Regulatory		USA	EU	
	PSTN		Part 68	TBR 21	
	EMC		FCC Part 15B	EN55032 & EN55024	
	RoHS	٠	Comply with directive 2002/95/EC RoHS	(as amended by commission decision 2005/613/EC)	
	Temperature	٠	Storage: Low temperature at -10°C	High temperature at +60°C	
		•	Operating: Low temperature at 0°C	High temperature at +40°C	

Model: ASP-6110-SF

