

DIGITAL VIDEO RECORDER

SERIES

960H

IDVR-4208ND

IDVR-4216ND

impaq
Live Free

960H DIGITAL VIDEO RECORDER

IDVR-4208ND

8 Channels 960H DVR



HIGHLIGHTS

8 Channels CIF Real Time & 960H DVR | High Resolution 240 x 200 in CIF, 120 x 100 in D1 & 960H with HDMI video output | 960H with 100fps for live image, recording with H.264 Compression | 2 Unit of Hard Disk 2TB Capacity | SMART feature with email notification | Made in Korea.

TECHNICAL SPECIFICATIONS

Video	Input Channel & Input Level Output Main Monitor Output Sub Monitor	8CH Composite, 1.0Vp-p, 75ohm VGA & HDMI (MAX. 1280 x 1024) CVBS or SPOT
Audio	Input & Output Audio Codec	4 Line Input & 1 Line Output G.711
Alarm	Sensor Input Alarm Output	4CH (NC/NO Selectable) 1 Alarm out by Sensor, Motion and Video Loss
Record	Compression Multi-operation Resolution Recording Mode Playback Speed (Single CH)	H.264 PENTAPLEX(Live/Playback/Record/ Network/Backup) 240/200fps(CIF), 120/100fps(D1), 120/100fps(960H) Continuous / Schedule / Motion / Sensor / Manual x 0.25, 0.5, 2, 4, 8, 16, 32, 64
Storage	HDD (Capacity of 1 HDD) E-SATA Port & USB Port POS PTZ & Keyboard Control	2TB x 2 Unit None E-SATA & 2EA (Front 1, Rear 1) None 1 RS-485
Serial Port	Dynamic DNS	Yes (Free DDNS)
Network	Web viewer	Live, Search, Backup, PTZF Cam Control, Remote Setup/Upgrade
Network Access	Client Software: UMS Single Multi-sites Monitoring System Watermarking	Live, Search, Backup, PTZF Cam Control, Remote Setup/Upgrade Live, Search, Backup, PTZF Cam Control, Remote Setup/Upgrade Yes
Features	NTP (Network Time Protocol) S.M.A.R.T 3G Mobile	Yes Yes iPhone / iPad / Android
Power	Power Supply Voltage	DC 12V 3A
Temperature	Operating Temperature	5°C - 40°C, During storage: -10°C - +50°C
Weight Dimension	Unit Weight Unit Dimension (W x H x D)	1.5 kg (3.0 kg) 340mm x 262mm x 63mm

DISTRIBUTED BY

